

KENWOOD



TK-7302(H)V/8302(H)U

Compact VHF/UHF FM Mobile Radios

FleetSync®

GENERAL FEATURES

- 25 / 50 W (136-174 MHz) Models
- 25 / 45 W (450-520 MHz) Models
- Conventional Zones
- 16 Channels / 2 Zones
- Single Priority Scan
- Single / Multi-Zone Scan
- 2-Digit LED Channel Display
- Function/Status LED Dots
- Blue Function/Status LED
- Transmit /Busy / Call Alert LED
- Backlit Keys
- 9 Programmable Function Keys
- Emergency / AUX Key
- Front Panel Speaker
- Companded Audio
- Voice CH# Announcement (8 Languages)
- Voice Inversion Scrambler Built-in
- 16 Scrambler Codes (per CH)
- Encryption / Board Control
- Emergency Call Features
- Lone Worker Alert

- QT / DQT
- Operator Selectable Tone
- Two-Tone Decode
- Single & Two-Tone Encode
- DTMF Encode / Decode
- Special Alert Tone Patterns
- Busy Channel Lockout
- Time Out Timer
- Timed Power Off
- DB15 Accessory Interface
- 8 Programmable I/O Ports
- Ignition Sense
- Public Address / Horn Alert Output
- MIL-Spec Standard Mic
- MIL-Spec 12-Key DTMF Mic Option
- Windows® Programming & Tuning
- Cloning
- MIL-STD-810 C/D/E/F
- IP-54 Water & Dust Intrusion

FleetSync® /II (FM)

- PTT ID Digital ANI
- Selective Call & Group Call
- Paging Call
- Status Messaging
- Emergency Status
- Input / Output Status Messages
- FleetSync® GPS Ready
- Send GPS PF Key
- PTT ID & Emergency GPS Reporting
- Ignition On/Off GPS Reporting

MDC-1200

- PTT ID Digital ANI
- Emergency Status
- Radio Check
- Radio Inhibit




Options

■ **KMC-35**
Microphone
(Supplied)



■ **KES-3**
External Speaker



■ **KLF-2**
Line Filter



■ **KCT-60**
DB 15-to-15 Pin
Molex Adaptor Cable



■ **KMC-36**
Microphone
with Keypad



■ **KES-5**
External Speaker
(requires KCT-60 option)



■ **KCT-18**
Ignition Sense Cable
(requires KCT-60 option)



■ **KMC-9C**
Desktop Microphone



■ **KMB-10**
Key Lock Adapter



■ **KCT-36**
3m Extension Cable
(for KCT-60)



All accessories and options may not be available in all markets.
Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Specifications

Model	TK-7302V	TK-7302HV	TK-8302U	TK-8302HU
GENERAL				
Frequency Range	136-174 MHz		450-520 MHz	
Number of Channels				
Zone	2			
Channel	Max. 16			
Channel Spacing	25 kHz/12.5 kHz			
Operating Voltage	13.6V DC±15%			
Current Drain				
Standby	0.4 A			
Receive	1.0 A			
Transmit	8.0 A	14.0 A	8.0 A	14.0 A
Operating Temperature Range	-22°F ~ +140°F (-30°C ~ +60°C)			
Frequency Stability	±2.5 ppm (-30°C ~ +60°C)			
Antenna Impedance	50 Ω			
Dimensions (W x H x D)				
Projections not included	6.3" x 1.7" x 5.4" (160 x 43 x 137 mm)			
Weight (Net)	41.6oz (1,180g)			
FCC ID	K44407600	K44407601	K44407700	K44407702

Specifications are subject to change without notice, due to advancements in technology.
FleetSync® is a registered trademark of JVC KENWOOD Corporation in the United States and/or other countries.
Windows® is a registered trademark of Microsoft Corporation in the United States and other countries.
All other trademarks are property of their respective owners.

Model	TK-7302V	TK-7302HV	TK-8302U	TK-8302HU
RECEIVER (Measurements made per TIA/EIA-603)				
Sensitivity (12dB SINAD)				
Wide	0.28 μV			
Narrow	0.35 μV			
Selectivity				
Wide	75 dB			
Narrow	65 dB			
Intermodulation Distortion				
Wide	70 dB			
Narrow	60 dB			
Spurious Response	75 dB			
Audio Output (4 Ω Impedance)	4 W with less than 5% distortion			
TRANSMITTER (Measurements made per TIA/EIA-603)				
RF Power Output	5 W ~ 25 W	5 W ~ 50 W	5 W ~ 25 W	5 W ~ 45 W*1
Spurious Response	70 dB			
Type of Emission				
Wide	16KØF3E			
Narrow	11KØF3E			
FM Hum & Noise				
Wide	45 dB			
Narrow	40 dB			
Microphone Impedance	600 Ω			
Audio Distortion	Less than 5%			

*1: 490 ~ 512 MHz: 5 ~ 40 W, 512 ~ 520 MHz: 5 ~ 35 W

Applicable MIL-STD & IP

Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I
Rain*2	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4
Salt Fog*2	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4
Dust*2	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I
Shock	516.2/Procedure I, II, III, V	516.3/Procedure I, IV, V	516.4/Procedure I, IV, V	516.5/Procedure I, IV, V
International Protection Standard				
Dust & Water Protection*2	IP54			

*2: These MIL-STD and IP54 compliance categories require a KMC-35/36 microphone to be connected; the DB-15 connector to have supplied cover installed and KCT-xx cables or external speakers installed.

KENWOOD

Kenwood U.S.A. Corporation
Communications Sector Headquarters
3970 Johns Creek Court, Suite 100, Suwanee, GA 30024-1265

Order Administration/Distribution
P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745

Kenwood Electronics Canada Inc.
Canadian Headquarters and Distribution
6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8
www.kenwood.ca



www.kenwoodusa.com



ISO9001 Registered
Communications Equipment Division
Professional Systems Business Group
JVC KENWOOD Corporation
ADS#28012 Printed in USA