

BSC-5000

Base Station Console

SPECIFICATION SHEET – NORTH AMERICA

Variable Base Configurations

The BSC-5000 is specifically designed for use with the VX-5500 or VX-6000 Series mobile radios to provide users greater choices in base station configurations for greater value.

One console, when combined with VX-5500 or VX-6000 mobile radios, gives you a choice of bands and power ranges for just the right base station solution for your operation and for maximum return on your investment.

Built-in Power Supply

Contains 30 Amp DC power supply capable of delivering enough power to run 120 W Low Band when used with the VX-6000 low band mobile radio.

Loud, Clear Audio

Includes front-mounted 12 W speaker for clear audio sound.

DC Power Back-Up Connectivity

Rear connection for DC back-up power input to support your critical operations in case you lose primary power.

Date and Time Indicator

Includes front panel LCD with 12-hour or 24-hour digital clock.

Accessories

- ▼ MD-12A8J: Desktop microphone
- ▼ FAN-1: Cooling fan

Mobile Radio Options	VX-5500L VX-6000L*	VX-5500V VX-6000V*	VX-5500U VX-6000U*
Frequency Range	29.7 – 37 MHz 37 – 50 MHz*	134 – 160 MHz 148 – 174 MHz*	400 – 430 MHz 450 – 490 MHz* 480 – 512 MHz*
Output Power	70 W	50 W	45 W



BSC-5000
(mobile radio sold separately)

General Specifications

Dimension (H x W x D)	4.8 x 16 x 14 inches (120 x 400 x 352 mm)
Weight (Approx.)	17.6 lbs (8 kg) without mobile radio



The Vertex Standard Difference

Our number one goal is achieving superior customer satisfaction by delivering products and services that exceed your expectations. Vertex Standard radios are built to last and are backed by an industry-leading 3 year warranty.