

KENWOOD

NEXEDGE®

NX-740HV/840HU

NEXEDGE® VHF/UHF Digital & FM Mobile Radios

NXDN® **FleetSync®**

It's true that analog radios are still playing a role in mobile communications. But the future is unquestionably digital, and the new NEXEDGE NX-740HV/840HU demonstrates why, offering increased effective coverage area, low noise for superior clarity, and inherent secured voice. As you would expect from KENWOOD, intuitive operation, high-powered performance, and round-the-clock reliability come as standard. But there's more. This mobile radio has a dual personality: it operates in both analog FM and NXDN digital modes, enabling smooth migration from legacy systems.

● NXDN DIGITAL AIR INTERFACE

NEXEDGE radios employ NXDN, an FDMA digital air interface with AMBE+2™ voice coding technology, unique filtering and a 4-level FSK modulation technique with low bit error rate (BER) even at weak RF signal strengths.

● ENHANCED AUDIO QUALITY

AMBE+2 VOCODER technology accurately replicates natural human speech nuances for superior voice quality, even at highway speeds. Additionally, the powerful 2-1/4" x 1-3/8" oval speaker delivers up to 4W (4Ω impedance) audio output, providing undeniably clearer and crisper audio.

● ULTIMATE PERFORMANCE

Maximum RF output power is 50W on the NX-740HV VHF model, 45W on the NX-840HU UHF model. Additionally, the UHF frequency coverage on the NX-840HU is 70 MHz.

● HIGH SECURITY

Confidentiality in radio communications is a KENWOOD priority, and helping to maintain a high level of security in analog mode is a 16-code voice inversion scrambler, while robust NXDN encryption is available in digital mode.

● 32 CHANNELS / 2 ZONES

This radio can be used with two conventional zones, offering up to 16 channels per zone.

● SWITCHABLE DIGITAL AND ANALOG DUAL MODES

The NX-740HV/840HU is effectively two radios in one – analog and digital – operating on 12.5/ 25* kHz in analog zones, and on 6.25/12.5 kHz NXDN in digital zones. For convenience, a PF key can be used to switch between zones.

*25 kHz is not included in the models sold in the USA or US territories.

● 6.25/12.5 kHz NXDN DIGITAL CHANNELS

Digital communications are more spectrum-efficient and offer wider area coverage than analog.

● NXDN DIGITAL CONVENTIONAL

Compatible with NEXEDGE Digital Conventional Mode, this radio offers 64 RAN (Radio Access Numbers) and individual & conference group calling to ensure expeditious communications.

● NXDN TYPE-D DIGITAL TRUNKING*

The NX-740HV/840HU supports the NXDN Type-D digital trunking protocol.* With this architecture, also known as distributed or decentralized trunking, all channels can operate as traffic channels without the need for a dedicated control channel. This makes it possible to develop an efficient and reliable yet affordable trunking system. Type-D trunking is thus suitable for users considering migration to a small-scale digital trunking system.

*Requires activation

● GPS FEATURE

Connecting a GPS unit to the NX-740HV/840HU enables you to transmit accurate vehicle location (GPS) data to the central base station for fleet management purpose.

● EXTERNAL D-SUB 15-PIN INTERFACE

The radio's D-Sub 15-pin terminal can be used to connect peripherals, enabling Ignition Sense, External Switch, Horn Alert, etc. Molex interface compatibility is provided by the optional KCT-60 cable.

● OTHER FEATURES

DIGITAL: • Over-The-Air Alias (TX only) • Paging Call • Individual Call & Conference Group Call • Status Messaging • Remote Monitor • Site Roaming • Late Entry • NXDN ESN

ANALOG: • FleetSync, MDC-1200, DTMF • QT/DQT/2-tone • Compander • Squelch Level

GENERAL: • Multiple Scan • 4-Color LED (Blue / Red / Green / Orange) • 9 PF Keys • Voice Announcement (select a language from English, Spanish, French, or Russian) • Emergency Call • Remote Stun/Kill • Lone Worker Alert • Time Out Timer • Busy Channel Lockout • Horn Alert • Ignition Sense • Wired Cloning • Password Protection • PTT Release Tone • Minimum Volume • Mic Sense • MIL-STD-810 C/D/E/F/G • IP54 Water & Dust Intrusion



Options

KMC-35 Microphone




KES-5 External Speaker (requires KCT-60 option)



KCT-60 DB 15-to-15 Pin Molex Adaptor Cable



KMB-34 Mounting Case for KPS-15



KMC-36 Microphone with Keypad



KCT-18 Ignition Sense Cable (Requires KCT-60 option)



KLF-2 Line Filter



KPS-15 DC Power Supply



KES-3S External Speaker



KCT-36 3m Extension Cable (for KCT-60)



KMB-10 Key Lock Adapter



Main Specifications

All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

		NX-740HV	NX-840HU
GENERAL			
Frequency Range		136-174 MHz	450-520 MHz
Number of Channels			Max. 32
Zones			2
Max. Channels per Zone			16
Channel Spacing	Analog	30*/25*/15/12.5 kHz	25*/12.5 kHz
	Digital		12.5*/6.25 kHz
Operating Voltage		13.6 V DC \pm 15%	
Operating Temperature Range		-22° F to +140° F (-30° C to +60° C)	
Frequency Stability		\pm 2.0 ppm	\pm 1.0 ppm
Antenna Impedance		50 Ω	
Dimensions (W x H x D)	Projections not included	6.29 x 1.69 x 4.82 in (160 x 43 x 122.6 mm)	
Weight (net)		2.42 lb (1.10 kg)	
FCC ID		K44452600	K44452700

Measurements made per CAI measurement procedures (digital) and TIA-603 (analog); specification are typical. Details and timing of firmware and software updates are subject to change without notice. Specifications are subject change without notice, due to advancements in technology.

FleetSync® is a registered trademark of JVCケンウッド Corporation.
 AMBE+2™ is a trademark of Digital Voice Systems Inc.
 Windows® is a registered trademark of Microsoft Corporation in the United States and other countries.
 NXDN® is a trademark of JVCケンウッド Corporation and Icom Inc.
 NEXEDGE® is a trademark of JVCケンウッド Corporation.

		NX-740HV	NX-840HU
RECEIVER			
Sensitivity	Digital @ 6.25 kHz (3% BER)		0.28 μ V
	Digital @ 12.5 kHz (3% BER)		0.28 μ V
	Analog (12 dB SINAD)		0.28 μ V
Selectivity	Analog @ 25*/12.5 kHz		75 / 65 dB
Intermodulation	Analog		70 dB
Spurious Response	Analog		75 dB
Audio Distortion			Less than 5 % distortion
Audio Output			4W / 4 Ω
TRANSMITTER			
RF Power Output	High / Mid / Low	50-5 W	45-5 W
Spurious Response			70 dB
FM Hum & Noise	Analog 25*/12.5 kHz		45 / 40 dB
Audio Distortion			Less than 5%
Modulation		16K0F3E, 11K0F3E, 4K00F1E, 4K00F1D, 4K00F7W 4K00F2D, 8K30F1E, 8K30F1D, 8K30F7W	

* Ver. 2.0 models are compatible with Analog 25 and 30 kHz as well as Digital 12.5 kHz Channel Spacing. However, Analog 25 and 30 kHz are not included in the models sold in the USA or US territories.

ACCESSORIES INCLUDED

- KMC-35 Microphone
- DC Cable
- Fuse
- Set of screws
- Mic. Hanger
- Bracket

Supplied accessories may vary depending on the market.

Applicable MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II	503.5/Procedure I
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
Rain*	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III	506.5/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4	507.5/Procedure II
Salt Fog*	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
Dust*	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I Cat.20
Shock	516.2/Procedure I, II, III, V	516.3/Procedure I, IV, V	516.4/Procedure I, IV, V	516.5/Procedure I, IV, V	516.6/Procedure I, IV, V
International Protection Standard					
Dust & Water Protection	IP54*				

*Required conditions: Microphone (KMC-35 or KMC-36) is connected; Cap shall be installed on the speaker connector; Cover shall be installed at D-sub connector (15pin); and KCT cable and/or SP cable are not connected.

KENWOOD

JVCケンウッド USA Corporation
 Communications Sector Headquarters

3970 Johns Creek Court, Suite 100, Suwanee, GA 30024-1265

Order Administration/Distribution

P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745

www.kenwood.com/usa



ISO9001 Registered
 JVCケンウッド Corporation

ADS#54415 Printed in USA