

NX-900/901

NEXEDGE®

NEXEDGE® 800/900 MHz Digital & Analog Mobile Radio

NXDN® MPT-1327 FleetSync®

● GENERAL FEATURES

- 15W (806-870 MHz) Model
- 15W (896-941 MHz) Model
- 512 CH-GID / 128 Zones
- Dash & Remote Mount
- Dual Control Head Remote Mount
- 14 Character Alphanumeric Aliases
- Backlit Dot Matrix LCD
- Function/Status LCD Icons
- Multi-Language Display
- Date & 12/24 Hour Time Clock
- Transmit/Busy/Call Alert/Warn LED
- On/Off Power Control
- 4 Up/Down Selectors
- 6 Front PF Keys
- Emergency/AUX Key
- 4W Speaker Audio
- DB-25 Accessory Connector
- 9 Programmable AUX I/Os
- 2 Programmable AUX Outputs
- KPG-111D Windows® FPU
- Flash Firmware Upgrading
- MIL-STD-810 C/D/E/F/G
- IP54/55 Water & Dust Intrusion
- PC Serial Interface
- SDM Manual Input¹
- Transparent Data Mode¹
- GPS Receiver Option
- VGS-1 Voice Guide / Voice & GPS Data Storage Option

● DIGITAL - GENERAL

- NXDN® Digital Air Interface
- AMBE+2™ VOCODER
- 6.25 & 12.5 kHz Channels
- Over-the-Air Alias
- Over-the-Air Programming
- Paging Call
- Emergency Call
- All Group Call
- Status Messaging¹
- Remote Stun/Kill¹
- Remote Check¹
- Short & Long Data Messages¹

● DIGITAL - GENERAL Cont.

- GPS Location with Voice¹
- NXDN® Scrambler Included
- DES Encryption Module Option
- AES & DES Encryption Module Option
- AES/DES Software Key Loader Option

● DIGITAL CONVENTIONAL MODE

- 64 Radio Access Numbers (RAN)
- Individual & Group Selective Call
- Mixed FM/Digital Operation
- Conventional IP Networks
- Site Roaming

● DIGITAL TRUNKING MODE

- Individual Private Call
- Group Call & Broadcast Call
- Telephone Interconnect
- Transmission Trunked Mode²
- Message Trunked Mode²
- Call Queuing with Priority²
- Late Entry (UID & GID)²
- 4 Priority Monitor ID's²
- Remote Group Add¹
- Failsoft Mode

● MULTI-SITE IP NETWORKS COMPATIBLE

- 60,000 GIDs / UIDs
- Wide Area Group Call
- Auto Roaming Registration
- Group Registration

● MULTI-SYSTEM COMPATIBLE

- 8 Trunked Networks³
- UID Lists for each network

● SCAN

- Single Zone / Multi-Zone / List Scan
- Dual Priority Scan (Conventional)

● ANALOG MODES - GENERAL

- 25* & 12.5 kHz Channels
- NPSPAC Channels*
- Conventional & LTR® Zones
- FleetSync®/II, MDC-1200, DTMF
- QT / DQT (Conventional Zones Only)
- Voice Inversion Scrambler
- Analog Scrambler Board Capability

● MPT ZONES**

- Single-Site Trunking
- Multi-Site Network Trunking
- 8 Network Capacity
- Network Roaming / Registration

● FleetSync®/II (FM)

- PTT ID ANI / Caller ID
- Selective / Group Call
- Emergency, Status & Text Messages¹

● MDC-1200

- PTT ID ANI / Caller ID
- Emergency, Radio Check & Inhibit

* 800 MHz model only.

** Optional



Options

KMC-35
Microphone



VGS-1
Voice Guide
& Storage Unit



KAP-2
Horn Alert
/ PA Relay Unit



KCT-46
Ignition Sense Cable



KMC-36
Microphone
with Keypad



KRK-10
Panel Remote Kit



KCT-23M
DC Cable (10 feet)



KMB-10
Key Lock Adapter



KMC-9C
Control Station
Desktop Microphone



KRK-13
Dual Control Head
Remote Kit



KCT-23M3
DC Cable (23 feet)



KLF-2
Line Noise Filter



KES-5
External Speaker



KPS-15
DC Power Supply



Main Specifications

All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

		NX-900	NX-901
GENERAL			
Frequency Range	Receive	851-870 MHz	935-941 MHz
	Transmit	806-825, 851-870 MHz	896-902, 935-941 MHz
Number of Channels		512	
Zones		128	
Max. Channels per Zone		250	
Channel Spacing	Analog	12.5 / 25 kHz	12.5 kHz
	Digital	6.25 / 12.5 kHz	6.25 / 12.5 kHz
Operating Voltage		13.6 V DC \pm 15%	
Operating Temperature Range		-22° F to +140° F (-30° C to +60° C)	
Frequency Stability		\pm 1.0 ppm	
Antenna Impedance		50 Ω	
Dimensions (W x H x D)	Projections not included	6.30 x 1.77 x 6.18 in (160 x 45 x 157 mm)	
Weight (net)		3.08 lb (1.40 kg)	
FCC ID		K44409300	K44409301
IC Certification		282F-409300	282F-409301

Analog measurements made per TIA/EIA 603 and specifications shown are typical. Specifications are subject to change without notice, due to advancements in technology.

FleetSync® is a registered trademark of JVC KENWOOD Corporation.

LTR® is a registered trademark of Transcript International.

AMBE+2™ is a trademark of Digital Voice Systems Inc.

Windows® is a registered trademark of Microsoft Corporation.

NXDN® is a registered trademark of JVC KENWOOD Corporation and Icom Inc.

NEXEDGE® is a registered trademark of JVC KENWOOD Corporation.

		NX-900	NX-901
RECEIVER			
Sensitivity	Digital @ 6.25 kHz (3% BER)	0.20 μ V	
	Digital @ 12.5 kHz (3% BER)	0.28 μ V	
	Analog (12 dB SINAD)	0.25 μ V	
Selectivity	Analog @ 25 kHz	75 dB	-
	Analog @ 12.5 kHz	68 dB	68 dB
Intermodulation	Analog	78 dB (\pm 50, 100 kHz)	
Spurious Response	Analog	80 dB	
Audio Distortion		Less than 3%	
Audio Output		4 W / 4 Ω	
TRANSMITTER			
RF Power Output		15 W to 5 W	
Spurious Response		70 dB	
FM Hum & Noise	Analog @ 25 kHz	45 dB	-
	Analog @ 12.5 kHz	40 dB	40 dB
Audio Distortion		Less than 3%	
Modulation		16K0F3E*, 14K0F3E*, 11K0F3E, 8K30F1E, 8K30F1D, 8K30F7W, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D	

Footnotes from front:

¹ Requires compatible PC software application or console.

² These trunked features are primarily system programming and operational dependent. Priority Monitor also requires NX subscriber settings.

³ Up to 8 different Trunked networks can be configured per radio (each in a zone)

* NX-900 only

Applicable MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II	503.5/Procedure I
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III	506.5/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4	507.5/Procedure II
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
Shock	516.2/Procedure I, II, III, V	516.3/Procedure I, IV, V	516.4/Procedure I, IV, V	516.5/Procedure I, IV, V	516.6/Procedure I, IV, V
International Protection Standard					
Dust & Water Protection	IP54: Radio itself				
	IP54/55: Remote head				

KENWOOD

Kenwood U.S.A. Corporation
Communications Sector Headquarters
3970 Johns Creek Court, Suite 100, Suwanee, GA 30024-1265

Order Administration/Distribution
P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745

Kenwood Electronics Canada Inc.
Canadian Headquarters and Distribution
6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8
www.kenwood.ca



www.kenwood.com



ISO9001 Registered
Professional Systems Business Group
JVC/KENWOOD Corporation

ADS#37413 Printed in USA