

# KENWOOD

Listen to the Future



## TK-2200L/3200L

Compact VHF/UHF FM Portable Radios

**FleetSync**<sup>®</sup>  
by KENWOOD



### GENERAL FEATURES

- 2 W (150-174 MHz) VHF
- 2 W (450-470 MHz) UHF
- 2, 8 & 15\* Channel Models
- Single Priority / Normal Scan
- Transmit / Busy / Call Alert / Scan / Warn LED
- 2 PF Keys
- Super Lock (Manager Key Lock)
- 500 mW Speaker Audio
- Enhanced Kenwood Audio
- Companded Audio
- Voice Annunciation
- VOX Ready
- Voice Inversion Scrambler Built-in
- QT / DQT
- DTMF Encode / Decode<sup>1</sup>
- 10 Call Alerting Tones
- Channel Confirmation Mode\*\*

- Time Out Timer
- Busy Channel Lockout
- Low Battery Warning
- Battery Saver
- Windows<sup>®</sup> Programming & Tuning<sup>2</sup>
- Wireless Cloning
- MIL-STD-810 C/D/E/F
- IP-54/55 Water & Dust Intrusion

### FleetSync<sup>®</sup>

- PTT ID Digital ANI
- Selective Call<sup>3</sup>

### ACCESSORIES INCLUDED

- KNB-45L Li-ion Battery
- KSC-35K 3-Hour Fast Charger
- KBH-10 Spring Action Belt Clip
- Removable Antenna

\*15 channel model is available in UHF only.

\*\*15 channel model only.

# Options

<ul style="list-style-type: none"> <li><b>KNB-45L</b> 2,000 mAh/7.4V Li-Ion Battery Pack</li> <li><b>KSC-35K</b> Fast Charger For the KNB-45L (3-Hour)</li> <li><b>KRA-22</b> VHF Low Profile Helical Antenna</li> <li><b>KRA-23</b> UHF Low Profile Helical Antenna</li> <li><b>KRA-26</b> VHF Helical Antenna</li> <li><b>KRA-27</b> UHF Whip Antenna</li> </ul>	<ul style="list-style-type: none"> <li><b>KRA-16</b> VHF Stubby Antenna</li> <li><b>KRA-17</b> UHF Stubby Antenna</li> <li><b>KMC-17</b> Speaker Microphone</li> <li><b>KMC-21</b> Compact Speaker Microphone</li> <li><b>KEP-2</b> Earphone Kit for KMC-17/21 (2.5mm plug)</li> <li><b>KHS-7</b> Single Muff Headset</li> </ul>	<ul style="list-style-type: none"> <li><b>KHS-7A</b> Single Muff Headset with In-line PTT</li> <li><b>KHS-8BL</b> 2-wire Palm Mic with Earphone (Black)</li> <li><b>KHS-8BE</b> 2-wire Palm Mic with Earphone (Beige)</li> <li><b>KHS-22</b> Behind-the-head Headset with PTT</li> <li><b>EMC-3</b> Clip Microphone with Earphone</li> </ul>	<ul style="list-style-type: none"> <li><b>HMC-3</b> Headset with PTT Built-in Vox</li> <li><b>KHS-23</b> 2-wire Palm Mic</li> <li><b>KMB-25</b> Six Unit Charger Adapter (for six KSC-35K chargers; (chargers not included)</li> <li><b>KBH-10</b> Belt Clip</li> <li><b>KWR-1</b> Water Resistance Bag</li> <li><b>KLH-126</b> Nylon Case</li> </ul>
--	--	--	---

All accessories and options may not be available in all markets.  
Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

# Specifications

Model	TK-2200L VHF	TK-3200L UHF
<b>GENERAL</b>		
Frequency Range	150-174 MHz	450-470 MHz
Number of Channels		
K Type	2	2
K2 Type	8	-
K3 Type	-	15
Channel Spacing		
Wide/Narrow	25, 30kHz/12.5, 15kHz	25kHz/12.5kHz
Channel Step	2.5, 5, 6.25, 7.5kHz	5, 6.25kHz
Operating Voltage	7.5V DC±20%	
Battery Life (5-5-90 duty cycle) with KNB-45L (2000mAh)	17 hours (Battery Saver Off) 22 hours (Battery Saver On)	
Operating Temperature Range	-22°F ~ +140°F (-30°C ~ +60°C)	
Frequency Stability	±2.5ppm (-22°F ~ +140°F)	
Antenna Impedance	50 Ω	
Channel Frequency Spread	24MHz	20MHz
Dimensions (W x H x D), Projections not Included		
Radio Only	2.13" x 4.8" x 0.83" (54 x 122 x 21.1mm)	
with KNB-45L	2.13" x 4.8" x 1.30" (54 x 122 x 33mm)	
Weight (net)		
Radio Only	5.6oz (160g)	
with KNB-45L	9.9oz (280g)	
FCC ID	ALH36913120	ALH36923130
FCC Compliance	Parts 22/74/90	Parts 90/95

Model	TK-2200L VHF	TK-3200L UHF
<b>RECEIVER (Measurements made per TIA/EIA-603)</b>		
Sensitivity (12dB SINAD)		
Wide/Narrow		0.25µV/0.28µV
Selectivity		
Wide/Narrow		70dB/60dB
Intermodulation Distortion		
Wide/Narrow		65dB/60dB
Spurious Response	65dB	60dB
Audio Output	500mW with less than 10% distortion	
<b>TRANSMITTER (Measurements made per TIA/EIA-603)</b>		
RF Power Output		
High/Low	2W/1W	2W/1W
Spurious Response	65dB	
Modulation		
Wide/Narrow	16KØF3E/11KØF3E	
FM Noise		
Wide/Narrow	45/40dB	
Audio Distortion	Less than 5%	

Kenwood follows a policy of continuous advancement in development.  
For this reason specifications may be changed without notice.

FleetSync® is a registered trademark of Kenwood Corporation.  
All other trademarks are property of their respective owners.

# Applicable MIL-STD & IP

Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures
<b>Low Pressure</b>	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II
<b>High Temperature</b>	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II
<b>Low Temperature</b>	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II
<b>Temperature Shock</b>	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II
<b>Solar Radiation</b>	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I
<b>Rain</b>	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III
<b>Humidity</b>	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4
<b>Salt Fog</b>	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4
<b>Dust</b>	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III
<b>Vibration</b>	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I
<b>Shock</b>	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV
<b>International Protection Standard</b>				
<b>Dust &amp; Water Protection</b>	IP54/55			

\*To meet MIL 810 and IP grade, the 2-pin connector cover has to be connected.

Footnotes from front:

<sup>1</sup> DTMF Encode: PTT ID, Auto-Dial (8 numbers); DTMF Decode: Code Squelch (3-10 digit), Group Codes A, B, C, D & Wild Card characters) and radio Stun.

<sup>2</sup> KPG-88D (version 2.0) required: Windows®98/ 2000/ Me/XP compatible; programs TK-2200/3200 ProTalk® models.

<sup>3</sup> ID List capacity: 8 ID's.

# KENWOOD

Kenwood U.S.A. Corporation  
Communications Sector Headquarters

3970 Johns Creek Court, Suite 100, Suwanee, GA 30024-1265

Order Administration/Distribution

P.O. BOX 22745, 2201 East Dominguez St., Long Beach, CA 90801-5745

Kenwood Electronics Canada Inc.  
Canadian Headquarters and Distribution

6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8



www.kenwoodusa.com



ISO9001 Registered  
Communications Equipment Division  
Kenwood Corporation  
ISO9001 certification

A5S#25609 Printed in USA